



| 公差/General Tolerances(mm) | |
|---------------------------|-------|
| 0 | >3 |
| ~ | >6 |
| ~ | >10 |
| ~ | >18 |
| ~ | >30 |
| ~ | >50 |
| ~ | >80 |
| ~ | >120 |
| ~ | >180 |
| ~ | >250 |
| ~ | >315 |
| ~ | >400 |
| ~ | >500 |
| ±0.12 | ±0.18 |
| ±0.22 | ±0.26 |
| ±0.31 | ±0.37 |
| ±0.57 | ±0.80 |
| ±0.93 | ±1.09 |
| ±1.15 | ±1.60 |
| ±2.20 | ±2.50 |
| 0.1/10 | ±2 |

| | | | |
|--|-----------------|--------|-------|
| UL 标准/UL Standard: | B | C | D |
| 额定电压/电涌/Rated Voltage(V)/Current(A) | 600/30 | 600/30 | 600/5 |
| EC 标准/IEC Standard: | | | |
| 过压类别/Overvoltage Category/污染等 | III/3 | / | / |
| 级/Pollution Degree | | | |
| 额定电压/电涌/Rated Voltage(V)/Current(A) | 800/41 | / | / |
| 额定电涌电压(KV)/Rete Impulse Voltage(KV) | 8.0 | / | / |
| 线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG) | 0.2~6/24~10(St) | | |
| 间距/Pitch(mm) | 8.0 | | |
| 剥线长度/Stripping length(mm) | 12~13 | | |
| 使用温度范围/Operating Temperature(°C) | -40~+105 | | |
| 符合RoHS环保要求/Conform to RoHS | Yes | | |
| 标识颜色编号/Standard color number: | / | | |
| PANTONE / RAL | / | | |
| MATERIAL: | SURFACE: / | | |

| | | | |
|------|-----------------|-----------------|-----------|
| 3 | Current Carrier | Copper | Sn Plated |
| 2 | Spring | Stainless Steel | |
| 1 | Housing | PA66 | UL94V-0 |
| ITEM | NAME OF PART | MATERIAL | NOTES |

| | |
|------------------------|-----------------------------------|
| MAT NO.: | / |
| STATUS: | / |
| APPD: Li GL | 2020.05.29 |
| CHKD: Mao J | 2020.05.29 |
| DRT: Wang Y2 | 2020.05.29 |
| SIZE: A4 | mm (inch) |
| TYPE: CUSTOMER DRAWING | SCALE: 1:1 SHEET 1/1 |
| NAME: | NINGBO DEGSON ELECTRICAL CO., LTD |
| DRAWING NO.: | WS6-C01 |
| REV | TO |

DEGSON® 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD
WS6-01P-1Y-00A(H)